
PMT-DAC12-4 (Isolated Analog Output Card)



Features

- 4 x 12-bit D/A output channels
- Multiple output ranges
- 2,500 V_{DC} isolation between the outputs and the PCI bus
- Keeps the output settings and values after system reset
- One DB37 connector for easy wiring
- Universal PCI and BoardID™ switch





Introduction

The PCI-1720U provides four 12-bit isolated digital-to-analog outputs for the Universal PCI bus. With isolation protection of 2500 V_{DC} between the outputs and the PCI bus, the PCI-1720U is ideal for industrial applications where high-voltage protection is required.

Specifications

Analog Output

Channels 4 isolated
Resolution 12 bits
Output Rate Static update

Output Range (Software programmable)

	Unipolar (V)	0 ~ 5, 0 ~ 10	
Internal Reference	Bipolar (V)	±5, ±10	
	Current Loop (mA)	0~ 20, 4 ~ 20	

Slew Rate 2 V/µs
Isolation Protection 2,500 V_{DC}
Driving Capability 5 mA
Operation Modes Software polling
Accuracy ±0.024%
Excitation Voltage 50 V (max.)

General

Bus Type Universal PCI 2.2
I/O Connectors 1 x DB37 female connector
Dimensions (L x H) 175 x 100 mm (6.9" x 3.9")

■ **Power Consumption** +5 V @ 350 mA (typical), 500 mA (max.) +12 V @ 200 mA (typical), 350 mA (max.)

• Operating Temperature $0 \sim 60^{\circ}$ C (32 $\sim 140^{\circ}$ F) (refer to IEC 68-2-1, 2)

• Storage Temperature $-20 \sim +70^{\circ} \text{ C } (-4 \sim 158^{\circ} \text{ F})$

• Storage Humidity 5 ~ 95% RH, non-condensing (refer to IEC 68-2-3)

Certifications

Ordering Information

• PCI-1720U 12-bit, 4-ch Isolated AO Universal PCI Card

PCL-10137-1 DB37 Cable, 1 m
PCL-10137-2 DB37 Cable, 2 m
PCL-10137-3 DB37 Cable, 3 m
ADAM-3937 DIN-rail Wiring Board

■ PCLD-880 Wiring Board w/ Two 20-pin Flat Cables & Adapter

Pin Assignments

NC	1	20	NC			
+12 Vout	2					
AGND	3	21	NC			
AGND	4	22	NC			
Vout 0	5	23	NC			
AGND	6	24	NC			
Isin k 0	7	25	NC			
		26	NC			
Vout 1	8	27	NC			
AGND	9	28	NC			
Isin k 1	10	29	NC			
Vout 2	11	30	NC			
AGND	12		NC			
Isin k 2	13	31				
Vout 3	14	32	NC			
AGND	15	33	NC			
Isin k 3	16	34	NC			
NC	17	35	NC			
		36	NC			
NC	18	37	NC			
NC	19					